

Product description:

EuroLam-Louvre windows System GG ISO 24 BT 50 (certified NRWG according to DIN EN 12101-2)

construction:

- Frame and blades in thermally separated three chamber aluminium profiles, made out of extruded aluminium sections, highly insulating
- Frame installation depth 50 mm
- No horizontal wing profile
- Total strength of wing 34 mm
- Louvre blades mounted in centre, excentric mounting also possible
- Variable height of louvre blades between 120mm and 300mm
- Hidden opening fittings

installation:

- Direct installation in masonry or with EuroLam- Clamping frame for installation in post-girt constructions, wall masonry(20 mm x clamping strength in mm) or window elements (30 mm x clamping strength in mm)
Thermally separated EuroLam- adapter sections made out of aluminium and/or plastic according to specific installation situation

glazing:

- Dry glazed
- Insulated glass insertable, made out of: 1x safety glass 6 – 8mm on the outside + safety glass 6 – 8mm on the inside

operation:

- Operation with pneumatic cylinders or electric servomotors with choice of 24V

Surface treatment:

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

Optional:

- Clamping protection class 4 over WPS
- Clamping protection class 3, Operation with LDE motor

manufacturer:

**EuroLam GmbH
Kupferstraße 1
99510 Wiegendorf
GERMANY**

info@eurolam.de
<http://www.eurolam.de>

Position description:

LV-Pos.

01	01 pcs	Louvre window	GG ISO 24 BT 50 NRWG
		Size (RAM) W x H:	_____x_____ mm
		Size clamping profile: (width x clamping strength)	_____x_____ mm
		Number of rows:	_____
		Number of louvre blades:	_____
		installation:	post-girt constructions, wall masonry or window elements
		glazing:	e.g.: ESG-H 6 mm 12 mm SZR ESG-H 6 mm
		operation:	24V; pneumatic cylinders
		Surface treatment:	RAL Standard

LV-Pos.

**EuroLam GmbH
Kupferstraße 1
99510 Wiegendorf
GERMANY**

info@eurolam.de
<http://www.eurolam.de>