#### Product description:

### EuroLam-Louvre windows System GG ISO 32 BT 60

#### Construction:

- Frame and blades in thermally separated three chamber aluminium profiles, made out of extruded aluminium sections, highly insulating
- Frame installation depth 60 mm
- No horizontal wing profile
- Total strength of wing 34 mm (bei 6mm äußere Glasscheibe)
- Louvre blades mounted in centre, excentric mounting also possible
- Variable height of louvre blades between 200 mm and 350 mm
- Hidden opening fittings

#### installation:

- Direct installation in mansory or with EuroLam- Clamping frame for installation in post-girt constructions, wall masonry(20 mm x clamping strength in mm) or window elements (30 mm x clamping strength in

Thermally separated EuroLam- adapter sections made out of aluminium and/or plastic according to specific installation situation

#### glazing:

- Dry glazed
- Insulated glass insertable, made out of: 1x safety glass 6 8mm on the outside + safety glass 6 8mm on the inside

(with black spacers) Ug-value depending on glass structure

Total strength of glass 32 mm

#### operation:

- Operation with manual crank handles, kinked connecting rods, pneumatic cylinders or electric servomotors with choice of 230V or 24V

### Surface treatment:

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

#### Optional:

- Clamping protection class 4 over WPS
- Clamping protection class 3, Operation with LDE motor

### manufracturer:

**EuroLam GmbH** Kupferstraße 1 99510 Wiegendorf **GERMANY** 

info@eurolam.de http://www.eurolam.de

## Position description:

## LV-Pos.

01	01 pcs	Louvre window	GG ISO 32 BT 60	SO 32 BT 60	
		Size (RAM) W x H:	X	mm	
		Size clamping profile: (width x clamping strength) Number of rows: Number of louvre blades:	x	mm	
		installation:	post-girt constructions, wall masonry or window elements		
		glazing:	e.g.: ESG-H 6 mm 12 mm SZR VSG 6 mm		
		operation:	Manual, 230 V; 24V; pneumatic cylinders		
		Surface treatment:	RAL Standard		

# LV-Pos.

EuroLam GmbH Kupferstraße 1 99510 Wiegendorf GERMANY

info@eurolam.de http://www.eurolam.de