

Product description:

EuroLam-Louvre windows System GG / ST BT 60

construction:

- Frame construction in non-insulated extrusion moulding aluminium profiles
- Frame installation depth 60 mm
- wings made out of point form glass pane with gloss finish
- Overlapping horizontal glass edges
- Hidden opening fittings

installation:

- elements with EuroLam adapter profiles for installation in post-girt constructions, wall masonry or window elements
adapter profiles made out of aluminium and/or plastic according to specific installation situation

glazing:

- Stepped safety glass 12 mm

operation:

- Operation with manual crank handles, kinked connecting rods, pneumatic cylinders or electric servomotors with choice of 230V or 24V

Surface treatment:

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

Optional:

- Clamping protection class 4 over WPS
- Clamping protection class 3, Operation with LDE motor

manufacturer:

**EuroLam GmbH
Kupferstraße 1
99510 Wiegendorf
GERMANY**

info@eurolam.de
<http://www.eurolam.de>

Position description:

LV-Pos.

| | | | |
|----|--------|--|--|
| 01 | 01 pcs | Louvre window | GG / ST BT 60 |
| | | size (RAM) W x H: | _____x_____ mm |
| | | size of clamping profile: (width x clamping strength) | _____x_____ mm |
| | | Number of rows: | _____ |
| | | Number of louvres: | _____ |
| | | installation: | post-girt constructions, wall masonry or window elements |
| | | glazing: | e.g.: Step-cascaded glass 12 mm |
| | | operation: | Manual, 230 V; 24V; pneumatic cylinders |
| | | Surface treatment: | RAL Standard |
| | | EuroLam GmbH Kupferstraße 1 99510 Wiegendorf GERMANY | |
| | | info@eurolam.de http://www.eurolam.de | |