

Product description:

EuroLam-Louvre windows System GG / OL BT 50

construction:

- Frame construction in non-insulated extrusion moulding aluminium profiles
- Frame installation depth 50 mm
- wings made out of point form glass pane with gloss finish
- Overlapping horizontal glass edges
- Hidden opening fittings

installation:

- Direct installation in masonry or with EuroLam- Clamping frame for installation in post-girt constructions, wall masonry(20 mm x clamping strength in mm) or window elements (30 mm x clamping strength in mm)
Thermally separated EuroLam- adapter sections made out of aluminium and/or plastic according to specific installation situation

glazing:

- safety glass 6 mm, 8 mm or 10 mm

operation:

- Operation with manual crank handles, kinked connecting rods, pneumatic cylinders or electric servomotors with choice of 230V or 24V

Surface treatment:

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

Optional:

- Clamping protection class 4 over WPS
- Clamping protection class 3, Operation with LDE motor

manufacturer:

**EuroLam GmbH
Kupferstraße 1
99510 Wiegendorf
GERMANY**

info@eurolam.de
http://www.eurolam.de

Position description:

LV-Pos.

01	01 Pcs	Louvre window	GG / OL BT 50
		Size (RAM) W x H:	_____x_____ mm
		Size of clamping profile: (width x clamping strength)	_____x_____ mm
		Number of rows:	_____
		Number of louvres:	_____
		installation:	post-girt constructions, wall masonry or window elements
		glazing:	e.g.: ESG-H 6
		operation:	Manual, 230 V; 24V; pneumatic cylinders
		Surface treatment:	RAL Standard
		EuroLam GmbH Kupferstraße 1 99510 Wiegendorf GERMANY	
		info@eurolam.de http://www.eurolam.de	