

Product description:

**EuroLam-Louvre windows System GG / ST BT 50**

**construction:**

- Frame construction in non-insulated extrusion moulding aluminium profiles
- Frame installation depth 50 mm
- wings made out of point form glass pane with gloss finish
- Overlapping horizontal glass edges
- Hidden opening fittings

**installation:**

- Direct installation in masonry or with EuroLam- Clamping frame for installation in post-girt constructions, wall masonry (20 mm x clamping strength in mm) or window elements (30 mm x clamping strength in mm)  
Thermally separated EuroLam- adapter sections made out of aluminium and/or plastic according to specific installation situation

**glazing:**

- Stepped safety glass 8 mm or 10 mm

**operation:**

- Operation with manual crank handles, kinked connecting rods, pneumatic cylinders or electric servomotors with choice of 230V or 24V

**Surface treatment:**

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

**Optional:**

- Clamping protection class 4 over WPS
- Clamping protection class 3, Operation with LDE motor

**manufacturer:**

**EuroLam GmbH  
Kupferstraße 1  
99510 Wiegendorf  
GERMANY**

info@eurolam.de  
<http://www.eurolam.de>

Position description:

**LV-Pos.**

01	01 Pcs	Louvre window	GG / ST BT 50
		Size (RAM) W x H:	_____ x _____ mm
		Size clamping profile: (width x clamping strength)	_____ x _____ mm
		Number of rows:	_____
		Number of louvres:	_____
		installation:	post-girt constructions, wall masonry or window elements
		glazing:	e.g.: step-cascaded glass 8 mm
		operation:	Manual, 230 V; 24V; pneumatic cylinders
		Surface treatment:	RAL Standard
		<b>EuroLam GmbH Kupferstraße 1 99510 Wiegendorf GERMANY</b>	
		info@eurolam.de <a href="http://www.eurolam.de">http://www.eurolam.de</a>	