

Product description:

EuroLam-Louvre windows System TGL ISO SLP BT 50 (certified NRWG according to DIN EN 12101-2)

construction:

- Frame and blades in thermally separated three chamber aluminium profiles, made out of extruded aluminium sections, highly insulating
- Frame installation depth 50 mm
- Louvre blades made out of thermally broken extruded aluminium sections
- Total thickness of louvre blade 38 mm
- Louvre blades mounted in centre, excentric mounting also possible
- Heights of Louvre blade 174, 192 and 200 mm
- Hidden opening fittings
- U_p -value 1,6 W/m²K

installation:

- Various adapter sections for installation in post-girt constructions, wall masonry or window elements
Thermally separated aluminium adapter profiles adapted to assembly options

operation:

- Operation pneumatic cylinders or electric servomotors of 24V

Surface treatment:

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

Optional:

- Clamping protection class 4 over WPS
- Clamping protection class 3, operation with LDE motor

manufacturer:

**EuroLam GmbH
Kupferstraße 1
99510 Wiegendorf
GERMANY**

info@eurolam.de
<http://www.eurolam.de>

Position description:

LV-Pos.

01	01 pcs	Louvre window size (RAM) W x H: size clamping profile: (width x clamping strength) Number of rows: Number of louvres: installation: operation: Surface treatment:	TGL ISO SLP BT 50 NRWG _____x_____ mm _____x_____ mm _____ _____ post-girt constructions, wall masonry or window elements 24V; pneumatic cylinders RAL Standard
		EuroLam GmbH Kupferstraße 1 99510 Wiegendorf GERMANY info@eurolam.de http://www.eurolam.de	