

Product description:

EuroLam-Louvre windows System TGL ISO SLP BT 60

construction:

- Frame and blades in thermally separated three chamber aluminium profiles, made out of extruded aluminium sections, highly insulating
- Frame installation depth 60 mm
- Louvre blades made out of thermally broken extruded aluminium sections
- Total thickness of louvre blade 48 mm
- Louvre blades mounted in centre, excentric mounting also possible
- Heights of louvre blade 174, 192 und 200 mm
- Hidden opening fittings
- U_p-value 1,1 W/m²K

installation:

- Various adapter sections for installation in post-girt constructions, wall masonry or window elements
Thermally separated aluminium adapter profiles adapted to assembly options

operation:

- Operation with manual crank handles, kinked connecting rods, pneumatic cylinders or electric servomotors with choice of 230V or 24V

Surface treatment:

- Profiles anodised, powder or wet paint coated to RAL, NCS, DB or special colour shades

Optional:

- Clamping protection class 4 over WPS
- Clamping protection class 3, operation with LDE motor

manufacturer:

**EuroLam GmbH
Kupferstraße 1
99510 Wiegendorf
GERMANY**

info@eurolam.de
<http://www.eurolam.de>

Position description:

LV-Pos.

01	01 pcs	Louvre window	TGL ISO SLP BT 60
		Size (RAM) W x H:	_____ x _____ mm
		Size lamping profile: (width x clamping strength)	_____ x _____ mm
		Number of rows:	_____
		Number of louvre blades:	_____
		installation:	post-girt constructions, wall masonry or window elements
		operation:	Manual, 230 V; 24V; pneumatic cylinders
		Surface treatment:	RAL Standard
		EuroLam GmbH Kupferstraße 1 99510 Wiegendorf GERMANY	
		info@eurolam.de http://www.eurolam.de	